

Accessories

for SITA bubble pressure tensiometers


Capillaries

for all tensiometers

Capillary PEEK type 1 – Laboratory standard

with high chemical resistance, easy to clean.

Applications e.g. in research and development of surfactants in cleaning and washing products as well as in quality assurance of inkjet inks, paints and coatings



Capillary PEEK type 2 – Process standard

Shape-optimized capillary with high chemical resistance and precise tip for high repeatability, reliable for permanent inline usage.

Applications e.g. in contaminated samples for process and bath control and monitoring surfactants in cleaning and electroplating processes



Capillary Glass type 3 – Special applications

Two-piece set with holder and borosilicate glass capillary with high chemical resistance. Special applications e.g. in chromic acid, chromo-sulphuric acid as well as chromatating baths



Disposable capillary PTFE – Special applications

Two-piece set with holder and PTFE disposable capillary with highest chemical resistance. Applications e.g. in adhesive products such as paints, coatings and liquid adhesives



Device protection

for all tensiometers to measure aggressive samples

Acid protection

glass protection for temperature probe, glass cover



Acid protection, glas-free

PFA protection for temperature probe, 2 PTFE beakers with PTFE cover



The acid protection for SITA DynoTester +, SITA pro line t15+ and SITA pro line t15 also includes a PE jacket for the tensiometer housing.

Desiccant

Drying column

(for SITA science line t100)

Desiccant cartridge

(for SITA science line t60)

with Drierite for drying the measuring gas and preventing condensation in the capillary in cold samples



Sample handling

for all tensiometers

Sample vessels (50 ml)

and suitable glass cover for sample measurement

Mini sample vessels (5 ml)

for measuring very small sample quantities



Temperature control vessel

for sample vessel (50 ml) to connect to a thermostat, including sample vessel, glass cover and insulation



Laboratory devices, compatible and automated with software SITA-LabSolution

for SITA pro line t15+, SITA pro line t15, SITA science line t100 and SITA science line t60

Automatic dispenser CAT Contibürette from μ 10D

for dosing of liquids from 10 μ l



Thermostat Lauda ECO RE 415S

for cooling and heating of the sample (-15...200 °C)



Thermostat Lauda ECO E4S

for heating of the sample (room temperature...200 °C)



Magnetic stirrer CAT M26

with heater, temperature sensor and stand



Kontakt

SITA Messtechnik GmbH
Gostritzer Straße 63
01217 Dresden
Germany

Tel. +49 (0)351 28853-0
info@sita-messtechnik.de
www.sita-messtechnik.de